© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

Wind sensor Standard



Specification	Order No.	Packing unit	GBP/piece without VAT	PS	EAN
	0913 00	-	-	-	4010337913009

Features

- The wind sensor enables e.g. blinds to be raised depending on the wind strength. In this way, sensitive blind slats can be protected from increasing wind.
- Recording and evaluating wind speeds.
- 8 adjustable wind strengths.
- Wind alarm is triggered 15 seconds after the set wind strength threshold is exceeded.
- Test run for function testing.
- Evaluation unit: Surface-mounted device for indoor installation in dry rooms.
- Wind transmitter: Device for outdoor installation.

Technical data

Wind transmitter	
- Material of the transmitter and cup anemometer:	Plastic (ABS), black
- Cup diameter:	Dia. 134, H 160
- Ambient temperature:	-20 °C to +55 °C
- Connection cable:	JY-ST-Y 2 x 0.6 mm², length 3 m (can be extended to max. 50 m)
- Protection class:	IP55
Evaluation unit	
- Wind warning range:	3.3 to 24.5 m/s, can be set to one of 8 levels
- Switching contact:	Relay with zero-voltage NO contact
- Load capacity:	max. 2 A
- Operating voltage:	AC 230?V
- Protection class:	IP20
Dimensions	
- W x H x D:	110 mm x 99 mm x 38 mm

Illustrations are similar and may deviate from originals.
Prices valid for United Kingdom with prices valid 01/26.

© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

Scope of supply

- Mounting bracket included with delivery.
