









Room climate sensor Standard for KNX System 55



Spezifikation	Bestell-Nr.	VE	GBP/Stück o. MWSt.	PS	EAN
 cream white glossy	2004 01	1/5	134.10	06	4010337130253
 pure white glossy	2004 03	1/5	134.10	06	4010337130260
 anthracite	2004 28	1/5	136.78	06	4010337130284
 pure white matt	2004 27	1/5	134.10	06	4010337130277
 colour aluminium	2004 26	1/5	139.46	06	4010337130291
 black matt	2004 005	1/5	139.46	06	4010337130307
 grey matt	2004 015	1/5	139.46	06	4010337130314
 stainless steel (lacquered)	2004 600	1/5	146.17	06	4010337130321

Merkmale

- Room climate sensor with integrates bus coupler.
- Room temperature auxiliary unit for a heating actuator with controller.
- Segment-based display: Display of the operating mode (comfort, lowering temperature, night-time lowering, eco), window status, operation lock, boost function, heating/cooling mode
- Display brightness can be configured incl. day/night mode.
- Integrated temperature sensor.

Operating functions

- Setpoint adjustment.
- Operating mode change.
- Operation lock can be set manually, automatically after a set time or via an object.
- Switch on/off function.
- Boost function.
- Heartbeat function: Check whether the application is running without errors.

Controller auxiliary unit

- Control of heating actuators for KNX with integrated controller.
- Change the operating mode of the room temperature controller.
- Adjust the target temperature of the room temperature controller.

Technische Daten

KNX medium:	TP256
KNX current consumption:	8 to 14 mA
KNX connection:	Connection and junction terminal
Protection class:	III
Installation depth:	19 mm
Ambient temperature:	-5 °C to +45 °C
Relative humidity:	5 to 95% (no condensation)

Hinweise

- KNX Data Secure compatible.
- Can be updated.
- Configuration and start-up of the device from ETS 5 version 5.7.7 or higher or ETS 6 version 6.3 or higher (recommended).

Lieferumfang

- KNX connection and junction terminal included in the scope of delivery.