© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

www.gira.com

**DALI potentiometer Tunable White**




| Specification | Order No. | Packing unit | GBP/piece without VAT | PS | EAN |
|---|---|---|---|---|---|
|  | 2020 00 | - | - | - | 4010337023463 |

**Features**

- Switching and brightness adjustment for lights with a DALI interface.
- Adjustment of the colour temperature for lights with a DALI device type 8 (colour type: colour temperature) for Tunable White in accordance with IEC 62386-209
- To generate the DALI voltage, a DALI power supply or a DALI potentiometer with an integrated power supply unit that conforms to the DALI specifications (DIN IEC 60926) is required.
- Can be operated simultaneously from several control points. Communication is via Broadcast.
- Colour temperature limits and a basic brightness or a switch-on brightness can be stored.

**Technical data**

| | |
|---|---|
| Current consumption: | max. 2 mA |
| Colour temperature adjustment: | 2000 to 10000K |
| Single-wire connection: | Max. 4 mm² |
| Installation depth: | 32 mm |
| Ambient temperature: | -5 °C to +45 °C |

**Notes**

- When selecting the DALI power supply, the number of DALI devices and the DALI potentiometer (always counts as 1 device) must be factored in.