© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

www.gira.com

DALI potentiometer with integrated power supply unit



Specification	Order No.	Packing unit	GBP/piece without VAT	PS	EAN
	2028 00	-	-	-	4010337023456

Features

- Switching and brightness adjustment for lights with a DALI interface.
- Integrated power supply in accordance with the DALI specifications (DIN IEC 60926) for 26 DALI devices.
- Parallel connection of up to 4 DALI potentiometers with integrated power supply unit to supply up to 104 DALI devices.
- Can be operated simultaneously from several control points. Communication is via Broadcast.
- A basic brightness or a switch-on brightness can be stored.

Technical data

Rated voltage:	AC 230 V, 50/60 Hz
Power consumption:	max. 2 W
DALI rated voltage:	DC 16 V (typ.)
Output current:	max. 52 mA
Number of DALI devices:	max. 26
Number of DALI potentiometers with integrated power supply unit that can be connected in parallel:	max. 4
Single-wire connection:	Max. 4 mm²
Installation depth:	32 mm
Ambient temperature:	-5 °C to +45 °C

Illustrations are similar and may deviate from originals.
Prices valid for United Kingdom with prices valid 01/26.

© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

Notes

- When selecting the DALI power supply, the number of DALI devices and the DALI potentiometer (always counts as 1 device) must be factored in.
