

## KNX Module for smoke alarm device Dual



| Spezifikation   | Bestell-Nr. | VE  | GBP/Stück o. MWSt. | PS | EAN           |
|---|-------------|-----|--------------------|----|---------------|
|  | 2343 00     | 1/5 | 126.97             | 46 | 4010337013518 |

### Merkmale

- The KNX module enables connection of the Dual Q smoke alarm device to a KNX system.
- Downwards-compatible, therefore it can also be used for smoke alarm device Dual/VdS.
- Alarm
- Auxiliary unit alarm (for networking several smoke alarm devices via KNX).
- Wired alarm (wired networking of several smoke alarm devices).
- Signal transmitter (to switch on signalling tone)
- Status messages.
- Fault messages.

### Technische Daten

|                      |                                  |
|----------------------|----------------------------------|
| KNX medium:          | TP256                            |
| KNX connection:      | Connection and junction terminal |
| Ambient temperature: | -5 °C to +50 °C                  |

### Hinweise

- The KNX module is easy to plug in at the interface of the Dual smoke alarm device. The networking terminals of the smoke alarm device can continue to be used when the module is attached.
- Please note the planning information in the "Technical Information" brochure, [www.download.gira.com](http://www.download.gira.com).
- The Gira AppShop is the marketplace for interesting solutions and applications in intelligent building technology. There are now more than 200 apps available, including application descriptions, plug-ins, function templates, logic nodes and sample projects. Discover applications for the KNX module for smoke alarm device Dual. [www.appshop.gira.de/en](http://www.appshop.gira.de/en).

## Lieferumfang

- Connection and junction terminal for KNX included with delivery.

---