# GIRA Data sheet

catalogue.gira.com

© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

www.gira.com

**Socket outlet with earth pin 16 A 250 V~, hinged cover and protección ampliada contra contacto accidental (Safety Plus) System 55**

| Specification | Order No. | Packing unit | GBP/piece without VAT | PS | EAN |
|---|---|---|---|---|---|
| cream white glossy | 4488 01 | 1/10 | 19.17 | 01 | 4010337095804 |
| pure white glossy | 4488 03 | 1/10 | 19.17 | 01 | 4010337095835 |
| pure white matt | 4488 27 | 1/10 | 19.17 | 01 | 4010337095859 |
| anthracite | 4488 28 | 1/10 | 20.36 | 11 | 4010337095866 |
| colour aluminium (lacquered) | 4488 26 | 1/10 | 24.57 | 11 | 4010337095842 |
| black matt (lacquered) | 4488 005 | 1/10 | 24.57 | 11 | 4010337095798 |
| grey matt (lacquered) | 4488 015 | 1/10 | 24.57 | 11 | 4010337095811 |
| stainless steel | 4488 600 | 1/5 | 32.12 | 11 | 4010337095873 |

Illustrations are similar and may deviate from originals.
Prices valid for United Kingdom with prices valid 01/26.

© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved



**Features**

- With plug terminals.
- The support ring is earthed in connection with the mounting claws and claw screws.
- Quick mounting (approx. 3.5 turns per mounting claw).
- Expanding claws in the housing.
- Easier claw mounting thanks to robust PZ1 / slotted / PH screw head drive.
- Simplified installation thanks to patented arrangement of the large keyhole profiles using box screws.
- Low installation depth.
- Large, ergonomically shaped release levers.
- Sturdy earth bar with solid earthing fingers.
- Sturdy and corrosion-resistant steel support ring.
- Shatter-proof thermoplastic base.

---

**Technical data**

| | |
|---|---|
| Installation depth: | 29 mm |
| Conductors: | Rigid and flexible |
| Connection cross section<br>- for conductors from: | <br>1.5 mm² to 2.5 mm² |
| Ambient temperature<br>- increased contact protection: | <br>0°C to +45°C |

---

**Notes**

- Approved in accordance with NF C 61-314:2017.
- Approved in accordance with NBN C 61-112-1:2017.
- Increased contact protection (Safety Plus) in accordance with DIN VDE 0620-1.

---