



Button with rocker, 2-gang for Gira One and KNX System 70



| Spezifikation | Bestell-Nr. | VE | GBP/Stück o. MWSSt. | PS | EAN |
|---|-------------|-----|---------------------|----|---------------|
|  pure white glossy | 5173 70 | 1/5 | 98.74 | 06 | 4010337116615 |
|  pure white matt (lacquered) | 5173 72 | 1/5 | 104.34 | 06 | 4010337116622 |
|  anthracite (lacquered) | 5173 73 | 1/5 | 104.34 | 06 | 4010337116592 |
|  black matt (lacquered) | 5173 74 | 1/5 | 104.34 | 06 | 4010337116639 |
|  grey matt (lacquered) | 5173 76 | 1/5 | 104.34 | 06 | 4010337116608 |

Merkmale

- Button for operating the Gira One system.
- Integrated temperature sensor for measuring the room temperature.
- Programming and start-up with the Gira Project Assistant (GPA), from version 5.0.
- Encrypted data transfer between the Gira One devices.

Operating functions

- Switching of devices, such as lights, socket outlets or pumps.
- Dimming of lights.
- Operation of shading and ventilation devices (blinds, shutters, skylights, roof domes and awnings).
- Convenient group control of switching, dimming, shading and ventilation devices.
- Calling up of scene variants.
- Use as a staircase button to activate the staircase function for switching and dimming devices.
- Floor-call button when combined with the Gira G1.
- Control of Sonos audio devices.
- Controls Hue devices.
- Control of eNet devices
- Door or garage door opener function.
- Boost function.

Room temperature

- Temperature adjustment for the integrated temperature sensor.

LED display

- Brightness value of the status LED can be set to 5 different levels, as well as off.
- Colour of the status LED (red, green, blue) can be set.
- Status LED function can be set depending on the rocker function: always OFF, always ON, actuation display or status display.

Technische Daten

| | |
|----------------------|-------------------------------------|
| Gira One Medium: | Twisted pair (TP), YCYM 2 x 2 x 0.8 |
| Test voltage: | 4 kV (KNX/EIB bus line) |
| Connection: | Connection and junction terminal |
| Protection class: | III |
| Installation depth: | 15 mm |
| Ambient temperature: | -5 °C to +50 °C |
| Current consumption: | 8 - 12 mA |

Hinweise

- Can be updated via the Gira Project Assistant (GPA)
 - The rockers are optionally interchangeable with alternative versions.
-