© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

System 3000 room temperature controller insertwith sensor connection



Specification	Order No.	Packing unit	GBP/piece without VAT	PS	EAN
	5395 00	1/5	102.91	02	4010337036128

Features

- Switching electric floor heating systems and thermal servos.
- Output signal: Pulse width modulation (PWM) or two-point control (On/Off).
- Input for switching over to cooling mode.
- Interrupts the heating process after 60 minutes (overheating protection of a heater).
- Connection of a remote sensor (accessory) possible.

Combination with RF Multi operating top unit, 1-gang / 2-gang for KNX

- Heating actuator, 1-gang
- Sensor channel, 1-gang or 2-gang.
- Local control of System 3000 insert possible.
- Wireless control of other devices for KNX possible as a sensor.
- Temperature detection.
- Insert function selection for room temperature controller:Control of 230 V servos, heating mode, cooling mode, heating and cooling mode, switchover to heating or cooling mode via communication object or auxiliary input. PWM and 2-point controller, absolute and relative setpoint setting, heating requirement control incl. cascading, valve protection function.Cyclical monitoring of the floor temperature, service mode for valve output, frost protection function (automatic or by communication object), temperature sensor calibration, boost function, summer and winter compensation.Auxiliary input is used for switching over between heating and cooling mode.

Technical data

Rated voltage:	AC 230 V, 50/60 Hz
Standby:	0.1 to 0.5 W
Switching current:	10 mA to 16 A
Connected load:	max. 3600 W
Recommended installation height:	1.50 m
Installation depth:	24 mm
Installation:	in device box in accordance with DIN 49073

Illustrations are similar and may deviate from originals.
Prices valid for United Kingdom with prices valid 01/26.

© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

Ambient temperature:	-5 °C to +45 °C