© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

www.gira.com

System 3000 auxiliary insert, 3-wire



Specification	Order No.	Packing unit	GBP/piece without VAT	PS	EAN
	5409 00	1/5	46.96	02	4010337048329

Features

- Auxiliary unit operation of inserts with auxiliary input from System 3000.
- Operation with suitable operating top unit from System 3000.
- Operation with neutral conductor connection.

Combination with RF Multi operating top unit, 1-gang / 2-gang for KNX

- Sensor channel 1-gang/2-gang.
- Wireless control of other devices for KNX possible as a sensor.
- Temperature detection.
- The three-wire auxiliary unit functions as a power supply for the RF Multi operating top unit 1-gang/2-gang for KNX.

Technical data

Rated voltage:	AC 230 V, 50/60 Hz
Standby - depends on top unit:	0.1 to 0.5 W
Cable length to the main unit:	max. 100 m
Installation depth:	24 mm
Installation:	in device box in accordance with DIN 49073
Ambient temperature:	-20 °C to +45 °C

Illustrations are similar and may deviate from originals.
Prices valid for United Kingdom with prices valid 01/26.

© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

Notes

- Can function as a mains-powered transmitter in conjunction with RF Multi operating top units for KNX and eNet operating top units.
