

System 3000 auxiliary insert, 3-wire



| Spezifikation | Bestell-Nr. | VE | GBP/Stück o. MWSt. | PS | EAN |
|---|-------------|-----|--------------------|----|---------------|
|  | 5409 00 | 1/5 | 46.96 | 02 | 4010337048329 |

Merkmale

- Auxiliary unit operation of inserts with auxiliary input from System 3000.
- Operation with suitable operating top unit from System 3000.
- Operation with neutral conductor connection.

Combination with RF Multi operating top unit, 1-gang / 2-gang for KNX

- Sensor channel 1-gang/2-gang.
- Wireless control of other devices for KNX possible as a sensor.
- Temperature detection.
- The three-wire auxiliary unit functions as a power supply for the RF Multi operating top unit 1-gang/2-gang for KNX.

Technische Daten

| | |
|-----------------------------------|--|
| Rated voltage: | AC 230 V, 50/60 Hz |
| Standby - depends on top unit: | 0.1 to 0.5 W |
| Cable length to the main unit: | max. 100 m |
| Installation depth: | 24 mm |
| Installation: | in device box in accordance with DIN 49073 |
| Ambient temperature: | -20 °C to +45 °C |

Hinweise

- Can function as a mains-powered transmitter in conjunction with RF Multi operating top units for KNX and eNet operating top units.
-