






## Room climate sensor Standard for KNX System 70



Spezifikation	Bestell-Nr.	VE	PS	EAN
 pure white glossy	2004 70	1/5		4010337130338
 pure white matt (lacquered)	2004 72	1/5		4010337130345
 anthracite (lacquered)	2004 73	1/5		4010337130352
 black matt (lacquered)	2004 74	1/5		4010337130369
 grey matt (lacquered)	2004 76	1/5		4010337130376

### Merkmale

- Room climate sensor with integrates bus coupler.
- Room temperature auxiliary unit for a heating actuator with controller.
- Segment-based display: Display of the operating mode (comfort, lowering temperature, night-time lowering, eco), window status, operation lock, boost function, heating/cooling mode
- Display brightness can be configured incl. day/night mode.
- Integrated temperature sensor.

### Operating functions

- Setpoint adjustment.
- Operating mode change.
- Operation lock can be set manually, automatically after a set time or via an object.
- Switch on/off function.
- Boost function.
- Heartbeat function: Check whether the application is running without errors.

## Controller auxiliary unit

- Control of heating actuators for KNX with integrated controller.
  - Change the operating mode of the room temperature controller.
  - Adjust the target temperature of the room temperature controller.
- 

### Technische Daten

KNX medium:	TP256
KNX current consumption:	8 to 14 mA
KNX connection:	Connection and junction terminal
Protection class:	III
Installation depth:	19 mm
Ambient temperature:	-5 °C to +45 °C
Relative humidity:	5 to 95% (no condensation)

---

### Hinweise

- KNX Data Secure compatible.
  - Can be updated.
  - Configuration and start-up of the device from ETS 5 version 5.7.7 or higher or ETS 6 version 6.3 or higher (recommended).
- 

### Lieferumfang

- KNX connection and junction terminal included in the scope of delivery.
-