

Room climate sensor HVAC Komfort for KNX System 55



Spezifikation	Bestell-Nr.	VE	PS	EAN
 cream white glossy	2007 01	1/5		4010337130758
 pure white glossy	2007 03	1/5		4010337130765
 pure white matt	2007 27	1/5		4010337130772
 anthracite	2007 28	1/5		4010337130789
 colour aluminium	2007 26	1/5		4010337130796
 black matt	2007 005	1/5		4010337130802
 grey matt	2007 015	1/5		4010337130819
 stainless steel (lacquered)	2007 600	1/5		4010337130826

Merkmale

- Room climate sensor with integrates bus coupler.
- Room temperature auxiliary unit for a heating actuator with controller.
- Segment-based display: Display of the operating mode (comfort, lowering temperature, night-time lowering, eco), window status, operation lock, fan level, heating/cooling mode, humidity and air quality status as a configurable traffic light indicator.
- Display brightness can be configured incl. day/night mode.

Technische Daten

KNX medium:	TP256
KNX current consumption:	8 to 14 mA
KNX connection:	Connection and junction terminal
Number of inputs:	4
Output voltage:	DC 5 V SELV
Output current:	Max. 3.2 mA
LED current:	2.2 mA per output
Length cable set:	25 cm, can be extended to max. 30 m
Protection class:	III
Installation depth:	19 mm
Ambient temperature:	-5 °C to +45 °C
Relative humidity:	5 to 95% (no condensation)

Hinweise

- KNX Data Secure compatible.
- Firmware can be updated using the Gira ETS Service App (additional software).
- Configuration and start-up of the device from ETS 5 version 5.7.7 or higher or ETS 6 version 6.3 or higher (recommended).

Lieferumfang

- Connection and junction terminal for KNX included with delivery.
 - 5-wire cable set
-