© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved



**DALI potentiometer with integrated power supply unit**




| Specification | Order No. | Packing unit | PS | EAN |
|---|---|---|---|---|
|  | 2028 00 | - | - | 4010337023456 |

**Features**

- Switching and brightness adjustment for lights with a DALI interface.
- Integrated power supply in accordance with the DALI specifications (DIN IEC 60926) for 26 DALI devices.
- Parallel connection of up to 4 DALI potentiometers with integrated power supply unit to supply up to 104 DALI devices.
- Can be operated simultaneously from several control points. Communication is via Broadcast.
- A basic brightness or a switch-on brightness can be stored.

**Technical data**

| | |
|---|---|
| Rated voltage: | AC 230 V, 50/60 Hz |
| Power consumption: | max. 2 W |
| DALI rated voltage: | DC 16 V (typ.) |
| Output current: | max. 52 mA |
| Number of DALI devices: | max. 26 |
| Number of DALI potentiometers with integrated power supply unit that can be connected in parallel: | max. 4 |
| Single-wire connection: | Max. 4 mm² |
| Installation depth: | 32 mm |
| Ambient temperature: | -5 °C to +45 °C |

Illustrations are similar and may deviate from originals.

© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved



**Notes**

- When selecting the DALI power supply, the number of DALI devices and the DALI potentiometer (always counts as 1 device) must be factored in.

---