© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

DALI potentiometer Tunable White with integrated power supply unit



Specification	Order No.	Packing unit	PS	EAN
	2030 00	-	-	4010337023470

Features

- Switching and brightness adjustment for lights with a DALI interface.
- Adjustment of the colour temperature for lights with a DALI device type 8 (colour type: colour temperature) for Tunable White in accordance with IEC 62386-209
- Integrated power supply in accordance with the DALI specifications (DIN IEC 60926) for 26 DALI devices.
- Parallel connection of up to 4 DALI potentiometers with integrated power supply unit to supply up to 104 DALI devices.
- Can be operated simultaneously from several control points. Communication is via Broadcast.
- Colour temperature limits and a basic brightness or a switch-on brightness can be stored.

Technical data

Rated voltage:	AC 230 V, 50/60 Hz
Power consumption:	max. 2 W
DALI rated voltage:	DC 16 V (typ.)
Output current:	max. 52 mA
Number of DALI devices:	max. 26
Number of DALI potentiometers with integrated power supply unit that can be connected in parallel:	max. 4
Colour temperature adjustment:	2000 to 10000K
Single-wire connection:	Max. 4 mm²
Installation depth:	32 mm
Ambient temperature:	-5 °C to +45 °C

Illustrations are similar and may deviate from originals.

© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

Notes

- When selecting the DALI power supply, the number of DALI devices and the DALI potentiometer (always counts as 1 device) must be factored in.
