© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

KNX Module for smoke alarm device Dual



Specification	Order No.	Packing unit	PS	EAN
	2343 00	1/5		4010337013518

Features

- The KNX module enables connection of the Dual Q smoke alarm device to a KNX system.
- Downwards-compatible, therefore it can also be used for smoke alarm device Dual/VdS.
- Alarm
- Auxiliary unit alarm (for networking several smoke alarm devices via KNX).
- Wired alarm (wired networking of several smoke alarm devices).
- Signal transmitter (to switch on signalling tone)
- Status messages.
- Fault messages.

Technical data

KNX medium:	TP256
KNX connection:	Connection and junction terminal
Ambient temperature:	-5 °C to +50 °C

Notes

- The KNX module is easy to plug in at the interface of the Dual smoke alarm device. The networking terminals of the smoke alarm device can continue to be used when the module is attached.
- Please note the planning information in the “Technical Information” brochure, www.download.gira.com.
- The Gira AppShop is the marketplace for interesting solutions and applications in intelligent building technology. There are now more than 200 apps available, including application descriptions, plug-ins, function templates, logic nodes and sample projects. Discover applications for the KNX module for smoke alarm device Dual.www.appshop.gira.de/en.

© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

Scope of supply

- Connection and junction terminal for KNX included with delivery.

Illustrations are similar and may deviate from originals.