© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

Switching actuator, 4-gang 10 A for KNX

Specification	Order No.	Packing unit	PS	EAN
DRA	5126 00	1		4010337138204

DRA switching actuators with integrated bus coupler. For switching independently controllable groups of loads. With manual switch for switching over the relay (On/Off) parallel or without KNX operation. Multi-phase connection. No additional power supply required.

Features

Switch outputs

- Input monitoring for cyclic updating of the switching object with safety position.

Logic functions

Technical data

KNX medium:	TP256
KNX current consumption:	
:	
Switching voltage:	
Current carrying capacity of adjacent outputs:	

Illustrations are similar and may deviate from originals.

© Copyright by
Gira Giersiepen GmbH & Co. KG
All rights reserved

Connections	
- KNX:	Connection and junction terminal
- Load:	
Ambient temperature:	-5 °C to +45 °C
Switching current	
- AC1 pursuant to DIN EN IEC 60947-4-1:	16 A
- Fluorescent lamps:	
- Maximum switch-on current:	
Loads per output	
- Light bulbs:	
- HV LED lamps:	100 W
- Motors:	

Notes

- KNX Data Secure compatible.
- Configuration and start-up of the device from ETS 5 version 5.7.7 or higher or ETS 6 version 6.3 or higher (recommended).
- KNX Data Secure compatible.
- Configuration and start-up of the device from ETS 5 version 5.7.7 or higher or ETS 6 version 6.3 or higher (recommended).

Scope of supply

- Switching actuator.
- Connection terminal for KNX.
- Secure Card.
- Operating instructions.
- Switching actuator.
- Connection terminal for KNX.
- Secure Card.
- Operating instructions.

Dimensions

Modular width (MW):	4

Illustrations are similar and may deviate from originals.